



Stainless steel reinforcement



Opening



Fixed

Elliptical Portlight 450 x 195 mm

Part no	Glass	Type	Function	Inner frame	Rec. hull thickness [mm]	Depth [mm]	Weight [gr]	Glass Thickness [mm]
A3120-190RF	Tinted	SS reinforcement	Opening	Stainless steel	8 - 15	15	1850	10
A3120-190CH	Tinted	SS reinforcement	Opening	Chrome	8 - 32	15	1750	10
A3120-190OW	Tinted	SS reinforcement	Opening	Off-white	8 - 32	15	1750	10
A3130-190RF	Tinted	SS reinforcement	Opening	Stainless steel	8 - 32	27	2060	10
A3130-190CH	Tinted	SS reinforcement	Opening	Chrome	8 - 32	27	1950	10
A3130-190OW	Tinted	SS reinforcement	Opening	Off-white	8 - 32	27	1950	10

Part no	Glass	Type	Function	Inner frame	Rec. hull thickness [mm]	Depth [mm]	Weight [gr]	Glass Thickness [mm]
A3320-190RF	Tinted	Regular	Opening	Stainless steel	8 - 32	15	1600	15
A3320-190CH	Tinted	Regular	Opening	Chrome	8 - 32	15	1500	15
A3320-190OW	Tinted	Regular	Opening	Off-white	8 - 32	15	1500	15
A3330-190RF	Tinted	Regular	Opening	Stainless steel	16 - 27	27	1800	15
A3330-190CH	Tinted	Regular	Opening	Chrome	27 - 44	27	1700	15
A3330-190OW	Tinted	Regular	Opening	Off-white	27 - 44	27	1700	15
A3125-190RF	Tinted	Regular	Fixed	Stainless steel	8 - 15	15	1350	10
A3125-190OW	Tinted	Regular	Fixed	Off-white	8 - 32	15	1500	10
A3135-190RF	Tinted	Regular	Fixed	Stainless steel	16 - 27	27	1470	10
A3135-190OW	Tinted	Regular	Fixed	Off-white	27 - 44	27	1750	10