



Stainless steel reinforcement



Opening



Fixed

Elliptical Portlight 485 x 225 mm

Part no	Glass	Type	Function	Inner frame	Rec. hull thickness [mm]	Depth [mm]	Weight [gr]	Glass Thickness [mm]
A3130-220RF	Tinted	SS reinforcement	Opening	Stainless steel	8 - 27	27	2250	10
A3130-220CH	Tinted	SS reinforcement	Opening	Chrome	8 - 54	27	2250	10
A3130-220OW	Tinted	SS reinforcement	Opening	Off-white	8 - 54	27	2250	10
A3150-220RF	Tinted	SS reinforcement	Opening	Stainless steel	28 - 47	47	2450	10
A3150-220CH	Tinted	SS reinforcement	Opening	Chrome	47 - 67	47	2450	10
A3150-220OW	Tinted	SS reinforcement	Opening	Off-white	47 - 67	47	1700	10

Part no	Glass	Type	Function	Inner frame	Rec. hull thickness [mm]	Depth [mm]	Weight [gr]	Glass Thickness [mm]
A3330-220RF	Tinted	Regular	Opening	Stainless steel	8 - 27	27	1950	15
A3330-220CH	Tinted	Regular	Opening	Chrome	8 - 54	27	1950	15
A3330-220OW	Tinted	Regular	Opening	Off-white	8 - 54	27	1950	15
A3350-220RF	Tinted	Regular	Opening	Stainless steel	28 - 47	47	2050	15
A3350-220CH	Tinted	Regular	Opening	Chrome	47 - 67	47	2050	15
A3350-220OW	Tinted	Regular	Opening	Off-white	47 - 67	47	2050	15
A3135-220RF	Tinted	Regular	Fixed	Stainless steel	8 - 15	27	1700	10
A3155-220RF	Tinted	Regular	Fixed	Stainless steel	28 - 47	47	1850	10