

## Hydraulic Integral Adjusters

CYLINDER	MODEL NO.	PISTON ROD SIZE		TENSION		CABLE/WIRE MAX. SIZE		PIN DIAMETER		LENGTH				STROKE	
		INCH	MM	LB	KG	INCH	MM	INCH	MM	CLOSED		OPEN		INCH	MM
-08 Standard	08SI	1/2"	12.7	3250	1477	1/4"	6.4	7/16"	11.1	21.9	555	30.8	781	8.9	226
-08 Long	08LI									26.0	660	38.8	987	12.9	327
-10 Standard	10SI	5/8"	15.9	4750	2152	9/32"	7.0	1/2"	12.7	23.0	584	32.5	824	9.5	241
-10 Long	10LI									27.0	686	40.5	1029	13.5	343
-10 Std Locking	10SLKI									39.0	990	47.5	1206	8.5	216
-10 Long Locking	10LLKI									48.0	1219	60.5	1536	12.5	318
-12 Standard	12SI	3/4"	19.0	6500	2945	5/16"	8.0	5/8"	15.9	24.0	609	34.0	863	10.0	254
-12 Long	12LI									28.0	711	42.0	1068	14.0	356
-12 Std Locking	12SLKI									40.0	1016	49.0	1244	9.0	229
-12 Long Locking	12LLKI									49.0	1244	62.0	1574	13.0	330
-17 Standard	17SI	3/4"	19.0	8750	3963	3/8"	9.6	5/8"	15.9	25.0	635	35.0	890	10.0	254
-17 Long	17LI									29.0	737	43.0	1092	14.0	356
-17 Std Locking	17SLKI									44.0	1178	53.0	1346	9.0	229
-17 Long Locking	17LLKI									53.0	1346	66.0	1676	13.0	330
-22 Standard	22SI	7/8"	22.0	11500	5209	7/16"	11.2	3/4"	19.0	29.0	737	40.0	1016	11.0	279
-22 Long	22LI									33.0	838	49.0	1244	16.0	408
-22 Std Locking	22SLKI									48.0	1219	58.0	1473	10.0	254
-22 Long Locking	22LLKI									57.0	1448	70.7	1795	13.8	319
-30 Standard	30SI	1"	25.4	20600	9332	1/2"	12.7	7/8"	25.4	34.0	864	45.0	1142	11.0	279
-30 Long	30LI									40.0	1016	56.5	1435	16.5	421

Data subject to change.