

## Chrome bronze rigging screws Toggle fork + Stud terminal, Split pin

Art. no.	Thread size UNF	Wire dia. mm	Length (L)		Clevis pin dia. mm	Toggle fork internal fork height, mm (H)	Internal fork width mm	Breaking load kN
			Min. mm	Max. mm				
174-321-39	1/4"	3	155	218	6,5	15	7	15.50
174-321-40	1/4"	4	155	218	6,5	15	7	15.50
174-322-39	5/16"	4	180	254	8	19	8	24.50
174-322-40	5/16"	5	192	266	8	19	8	24.50
174-323-39	3/8"	5	224	312	9,5	22	10	34.50
174-323-40	3/8"	6	223	311	9,5	22	10	34.50
174-324-39	7/16"	6	252	361	11	23,5	12	47.50
174-324-40	7/16"	7	252	361	11	23,5	12	47.50
174-325-39	1/2"	7	287	415	13	30	14	62
174-325-40	1/2"	8	284	412	13	30	14	62
174-326-39	5/8"	8	335	480	15,8	39,5	18	95
174-326-40	5/8"	10	340	485	15,8	39,5	18	95
174-327-39	3/4"	10	403	575	15,8	40,5	20	125
174-327-40	3/4"	12	405	577	15,8	40,5	20	125
174-327-41	3/4"	10	403	575	19	40,5	20	125
174-327-42	3/4"	12	405	577	19	40,5	20	125
174-328-39	7/8"	12	486	687	19	55	25	180
174-328-40	7/8"	14	494	695	19	55	25	180
174-328-41	7/8"	12	486	687	22	55	25	180
174-328-42	7/8"	14	494	695	22	55	25	180

